

Below-Deck Equipment (BDE) Form Factor	Standalone	Standalone	Standalone or Rack Mount	Standalone or Rack Mount	Rack Mount
Telephony Number of Voice Lines Determined by partner implementation	x 2	x 3	x 3	x 3	x 3
IP Data, Background All best-effort, maximum speeds Vessel Receive Vessel Transmit	88 kbps 88 kbps	176 kbps 176 kbps	352 kbps* 352 kbps*	704 kbps 352 kbps	1408 kbps 528 kbps
IP Data, Streaming Upload / Download Rate	56 kbps	128 kbps	256 kbps	256 kbps	256 kbps
Target Markets	Commercial FishingSport FishingLeisure SailingGMDSS**	 Commercial Fishing Tugs, Tows & River Craft Leisure Motor & Sail Sport Fishing GMDSS** 	Merchant ShippingCommercial FishingWork BoatGMDSS**	 Merchant Shipping Commercial Fishing Large Leisure Work Boat GMDSS** 	Offshore PlatformsScientific ResearchCruise & FerryYachtGMDSS**

^{*134} kbps on Iridium legacy satellites

The Iridium Certus Maritime Product Portfolio is being developed by third-party manufacturers and as such, is indicative and subject to change. Services are determined by partner implementation.

^{**}Pending IMO recognition